



1. Identification

Product identifier	BEHR® Interior/Exterior Flat Masonry, Stucco & Brick Paint - White
Other means of identification	
Product number	270
Recommended use	Architectural Coating
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/	Distributor information
Supplier	Behr Process Canada, Ltd.
	2750 Centre Avenue N.E.
	Calgary, AB T2A 2L3
Emergency telephone	(US)+1 760 476 3962
	(US)+1 866 519 4752
Access code	335213
2. Hazard identification	
Physical hazards	Not classified.
Health hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Other hazards	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Kaolin, calcined		92704-41-1	10 - 30
Titanium dioxide		13463-67-7	5 - 10
Quartz (SiO2)		14808-60-7	0.1 - 1
Composition comments	All concentrations are in percent by weight ur	nless ingredient is a gas. Gas	s concentrations are i

percent by volume.The exact concentrations of the above listed chemicals are being withheld as a trade secret.**4. First-aid measures**InhalationMove to fresh air. Call a physician if symptoms develop or persist.Skin contactWash off with soap and water. Get medical attention if irritation develops and persists.Eye contactRinse with water. Get medical attention if irritation develops and persists.IngestionRinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7 Llowelling and standard	

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Observe good industrial hygiene practices.
Conditions for safe storage,	Store in tightly closed container. Store away from incompatible materials (see section 10 of the
including any incompatibilities	SDS).

8. Exposure controls/personal protection

upational exposure limits US. ACGIH Threshold Limit Valu	165		
Components	Туре	Value	Form
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada Alborta OELs (Occupat	ional Health & Safety Code, Scl	nodulo 1. Table 2)	
Canada. Alberta OELS (Occupat	ional meanin & Salety Coue, Sci		
· · ·	Type	Value	Form
Quartz (SiO2) (CAS 14808-60-7)		, ,	Form Respirable particles.

Components	Туре	Value	Form
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Canada. Manitoba OELs (Components	Reg. 217/2006, The Workplace Safety An Type	d Health Act) Value	Form
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
	ontrol of Exposure to Biological or Chen		F
Components	Туре	Value	Form
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Quebec OELs. (N	linistry of Labor - Regulation respecting	occupational health and sa	
Components	Туре	Value	Form
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety Reg Type	gulations, 1996, Table 21) Value	Form
	8 hour	0.05 mg/m3	Respirable fraction.
Quartz (SiO2) (CAS 14808-60-7)	8 1001		
. , .	15 minute	20 mg/m3	
14808-60-7) Titanium dioxide (CAS		· ·	
14808-60-7) Titanium dioxide (CAS	15 minute	20 mg/m3 10 mg/m3	
14808-60-7) Titanium dioxide (CAS 13463-67-7)	15 minute 8 hour	20 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be al exhaust ventilation, or othe ended exposure limits. If expo	r engineering controls to
14808-60-7) Titanium dioxide (CAS 13463-67-7) ogical limit values ropriate engineering trols	15 minute 8 hour No biological exposure limits noted for t Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm	20 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be cal exhaust ventilation, or othe ended exposure limits. If expo an acceptable level. nt	r engineering controls to
14808-60-7) Titanium dioxide (CAS 13463-67-7) ogical limit values ropriate engineering trols	15 minute 8 hour No biological exposure limits noted for t Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm established, maintain airborne levels to s, such as personal protective equipmer	20 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be cal exhaust ventilation, or othe ended exposure limits. If expo an acceptable level. nt	r engineering controls to
14808-60-7) Titanium dioxide (CAS 13463-67-7) ogical limit values ropriate engineering trols vidual protection measure Eye/face protection	15 minute 8 hour No biological exposure limits noted for t Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm established, maintain airborne levels to s, such as personal protective equipmer	20 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be cal exhaust ventilation, or othe ended exposure limits. If expo an acceptable level. ht or goggles).	r engineering controls to
14808-60-7) Titanium dioxide (CAS 13463-67-7) ogical limit values propriate engineering trols vidual protection measure Eye/face protection Skin protection	15 minute 8 hour No biological exposure limits noted for t Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm established, maintain airborne levels to s, such as personal protective equipmer Wear safety glasses with side shields (or	20 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be cal exhaust ventilation, or othe ended exposure limits. If expo an acceptable level. ht or goggles).	r engineering controls to
14808-60-7) Titanium dioxide (CAS 13463-67-7) ogical limit values ropriate engineering trols vidual protection measure Eye/face protection Skin protection Hand protection	15 minute 8 hour No biological exposure limits noted for f Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm established, maintain airborne levels to s, such as personal protective equipmer Wear safety glasses with side shields (or Wear appropriate chemical resistant glo	20 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be ended exposure limits. If expo an acceptable level. nt or goggles). oves. s above the exposure limit the ssure air-supplied respirator if re not known, or any other cir	er engineering controls to osure limits have not beer ey must use appropriate there is any potential for
14808-60-7) Titanium dioxide (CAS 13463-67-7) ogical limit values ropriate engineering trols vidual protection measure Eye/face protection Skin protection Hand protection Other	15 minute 8 hour No biological exposure limits noted for f Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm established, maintain airborne levels to is, such as personal protective equipmer Wear safety glasses with side shields (of Wear appropriate chemical resistant glo Wear suitable protective clothing. When workers are facing concentration certified respirators. Use a positive-pres uncontrolled release, exposure levels a	20 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be al exhaust ventilation, or othe ended exposure limits. If expo an acceptable level. nt or goggles). oves. s above the exposure limit the ssure air-supplied respirator if re not known, or any other cir e adequate protection.	er engineering controls to osure limits have not beer ey must use appropriate there is any potential for

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity		
Components	Species	Test Results
Quartz (SiO2) (CAS 14808-60-7)		
<u>Chronic</u>		
Inhalation		
LOEC	Human	0.0563 mg/m3
Titanium dioxide (CAS 13463-67-7)	
<u>Acute</u>		
Inhalation	_	
LC50	Rat	3.43 mg/l, 4 Hours
Oral	_	
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitisation	1	
Canada - Alberta OELs: Irrita	ant	
Titanium dioxide (CAS 13	463-67-7)	Irritant
Respiratory sensitisation	Not a respiratory sensitiser.	
Skin sensitisation	This product is not expected to	o cause skin sensitisation.
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	roduct or any components present at greater than 0.1% are
Carcinogenicity	Due to the form of the product expected.	, exposure to the potentially carcinogenic components is not
ACGIH Carcinogens		
Quartz (SiO2) (CAS 1480		A2 Suspected human carcinogen.
Titanium dioxide (CAS 13 Canada - Alberta OELs: Card		A4 Not classifiable as a human carcinogen.
Quartz (SiO2) (CAS 1480	• • •	Suspected human carcinogen.
Canada - Manitoba OELs: ca		ouspected human carenogen.
Quartz (SiO2) (CAS 1480		Suspected human carcinogen.
Titanium dioxide (CAS 13		Not classifiable as a human carcinogen.
Canada - Quebec OELs: Car		
Quartz (SiO2) (CAS 1480	8-60-7) Evaluation of Carcinogenicity	Suspected carcinogenic effect in humans.
Quartz (SiO2) (CAS 1480		1 Carcinogenic to humans.
Titanium dioxide (CAS 13		2B Possibly carcinogenic to humans.
	gram (NTP) Report on Carcine	-
Quartz (SiO2) (CAS 1480	,	Known To Be Human Carcinogen.
Reproductive toxicity		o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be h	narmful.
12. Ecological information		
Ecotoxicity	Harmful to aquatic life with lon	g lasting effects.
Persistence and degradability	No data is available on the de	gradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects	No data available.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act Not regulated. Export Control List (CEPA 1999, Schedule 3) Not listed. Greenhouse Gases Not listed. Precursor Control Regulations Not regulated. International regulations Stockholm Convention Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable. Basel Convention

Not applicable.

16. Other information

Issue date	26-May-2020
Revision date	-
Version No.	01

List of abbreviations	 IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG Code: International Maritime Dangerous Goods Code. LC50: Lethal Concentration, 50%. LD50: Lethal Dose, 50%. LOEC: Lowest Observed Effect Concentration. MARPOL: International Convention for the Prevention of Pollution from Ships.
	TDG: Transportation of Dangerous Goods. TWA: Time Weighted Average Value.
References	HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens
Disclaimer	Behr Process Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.