

## **SAFETY DATA SHEET**

### **1. Product and Company Identification**

**Product Name:** Lube it All  
**Product Code:** LA12, LA01, LA06.  
**Product Use:** Penetrant

**Product Type:** Aerosol

**Manufacturer:** Federal Process Corp.      **Revision Date:** 3/26/2018  
**Address:** 4520 Richmond Road  
Cleveland, Ohio 44128      **Phone:** 1-800-846-2080  
**Emergency Phone Number:** Call Chemtrec at 1-800-424-9300

**NOTE:** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

### **2. Hazards Identification**

#### **GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Extremely flammable aerosol	Category 1
Gases under pressure	Compressed Gas
Aspiration Hazard	Category 1
Skin Irritation	Category 2
Eye Irritation	Category 2A

#### **Label Elements**

#### **Pictograms**



**Signal Word:** **Danger:**

#### **Hazard Statements:**

H222 Extremely flammable aerosol  
H229 Pressurized container: may burst if heated  
H280 Contains gas under pressure, may explode if heated  
H304 May be fatal if swallowed and enters airways  
H319 Causes serious eye irritation  
H315 Causes skin irritation

## Precautionary Statements:

### Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn
- P264 Wash thoroughly after handling
- P280 Wear protective gloves and eye protection

### Response:

- P301+P310 If Swallowed: Immediately call a poison center or doctor
- P331 Do not induce vomiting
- P302+P352 If on skin: Wash with plenty of soap and water.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P264 Take off contaminated clothing and wash it before reuse
- P305+P351  
+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention
- P410+P412  
+P403 Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F
- P501 Dispose of contents/container in accordance with local/regional regulations

## 3. Composition / Information on Ingredients

Ingredients	CAS #	Percent
Carbon Dioxide	124-38-9	.1-10 %
Distillates, petroleum, hydrotreated light	64742-47-8	25-35%
Petroleum Oil	64742-52-5	45-55%
Aliphatic Petroleum Distillate	64742-88-7	15-25%

## 4. First Aid Measures

### Eye Contact:

Flush with warm water for 15 minutes. Seek medical attention.

### Skin Contact:

Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.

### Inhalation:

Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

### Ingestion:

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce

vomiting. If possible, do not leave individual unattended.

## 5. Fire Fighting Measures

**Flash Point:** Flash point of liquid portion 104°F

**Flammable limits liquid portion @ 77 deg:**

Upper: 5.6.

Lower: 0.7

**Auto-ignition temperature of liquid portion 689F**

**Extinguishing Media:**

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

**Unusual Fire & Explosion Hazards:**

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

**Special Fire Fighting Procedures:**

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

## 6. Accidental Release Measures

**Spill or Leak Instructions**

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

## 7. Handling and Storage

**Handling:**

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water

after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

**Storage:**

Store in a cool, dry area, away from heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

## **8. Exposure Controls / Personal Protection**

**Protective Equipment:**

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

**Engineering Controls:**

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

**Respiratory Protection:**

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above exposure levels an approved self-contained breathing apparatus or airline respirator with full face-piece is required

**Other Suggested Equipment:**

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

**Discretion Advised:**

We take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

**Exposure guidelines:**

<b>Ingredients</b>	<b>CAS #</b>	<b>Percent</b>	<b>Exposure Limits</b>
Carbon Dioxide	124-38-9	.1-10 %	OSHA (PEL) 5000 ppm ACGIH TLV 5000 ppm
Distillates, petroleum, hydrotreated light	64742-47-8	25-35%	Supplier (TWA) 100 ppm
Petroleum Oil	64742-52-5	45-55%	TVL Oil Mist 5mg/m3
Aliphatic Petroleum Distillate	64742-88-7	15-25%	Supplier (TWA) 100 ppm

## **9. Physical and Chemical Properties**

**Boiling Point:** NA

**Specific Gravity:** <1

**Vapor Density:** >1(Air=1)

**Water Solubility:** Negligible

**Odor/Appearance:** Clear mist as dispensed from aerosol can.

**Evaporation Rate:** Ether = 1 Slower

## 10. Stability and Reactivity

**Stability:** Stable

**Conditions to Avoid:** Heat, spark, and open flame

**Incompatibility:** Strong-Oxidizing Agents

**Hazardous Decomposition:** Combustion will produce Carbon Monoxide, Carbon Dioxide and hydrocarbons..

**Hazardous Polymerization:** Will not occur

## 11. Toxicological Information

### Component Toxicological Information:

#### Mixture

This product may be an irritant to skin. This product may be severely irritating to the eyes.

#### Aliphatic Petroleum Distillate

Acute Oral	LD50 Rat	>5,000 mg/kg
Acute Inhalation	LC50 Rat (4 hour)	>4.3 mg/l
Acute dermal	LD50 rabbit:	2,000 – 4,000 mg/kg

#### Distillates, petroleum, hydrotreated light

Acute Oral	LD50 Rat	>5,000 mg/kg
Acute Inhalation	LC50 Rat (4 hour)	>6.8 mg/l
Acute dermal	LD50 rabbit:	2,000 – 4,000 mg/kg

## 12. Ecological Information

The information given is based on data available for the material, the components of the material, and similar materials.

### ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

Material -- Not expected to demonstrate chronic toxicity to aquatic organisms.

### PERSISTENCE AND DEGRADABILITY

**Biodegradation:** Material -- Expected to be readily biodegradable.

**Hydrolysis:** Material -- Transformation due to hydrolysis not expected to be significant.

**Photolysis:** Material -- Transformation due to photolysis not expected to be significant.

**Atmospheric Oxidation:** Material -- Expected to degrade rapidly in air

## 13. Disposal Considerations

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

## 14. *Transport Information*

DOT  
Consumer Commodity ORM-D

AIR (IATA)  
ID8000 Consumer Commodity

Vessel  
Aerosol (Limited Quantity), Class 2.1, UN1950, ERG126

## 15. *Regulatory Information*

### Environmental Regulations

#### Clean Water Act/Oil Pollutions Act:

#### SARA 302/304:

None

#### SARA 311/312:

Immediate ( x ) Delayed ( ) Fire ( x ) Reactive ( ) Sudden Release of Pressure ( x )

#### Section 313

#### Toxic chemical list:

All the chemicals used in this product are TSCA listed.  
Check with your local regulators to be sure all local regulations are met.

## 16. *Other Information*

**Hazard ratings** This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

Level 3 Aerosol

**HMIS:** Health: 2 Flammability: 3 Reactivity: 0

RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

#### Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do

not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.