

## **TURBO POWER ALL SEASON Antifreeze/Coolant**

#### **SECTION 1. IDENTIFICATION**

Product Identifier TURBO POWER ALL SEASON Antifreeze/Coolant

Other Means of 86-249

Identification

**Recommended Use** Please refer to Product label.

Restrictions on Use None known.

Manufacturer / Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory

Supplier Department, 905-878-5544, www.recochem.com

Emergency Phone No. CANUTEC, 613-996-6666, 24 Hours

**SDS No.** 0749

## **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Acute toxicity (Oral) - Category 4; Reproductive Toxicity - Category 1B

#### **GHS Label Elements**





Signal Word: Danger

## Hazard Statement(s):

H302 Harmful if swallowed.

H360 May damage the unborn child if inhaled, following skin contact and/or if swallowed.

H360 May damage fertility if inhaled, following skin contact and/or if swallowed.

## Precautionary Statement(s):

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash hands and skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

P330 Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Product Identifier: TURBO POWER ALL SEASON Antifreeze/Coolant

SDS No.: 0749 Page 01 of 08

#### Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

#### Other Hazards

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Ethylene glycol	107-21-1	60-100	
Sodium Salt of Boron Acid	CBI*		

#### **Notes**

CBI = Confidential Business Information. The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

#### **SECTION 4. FIRST-AID MEASURES**

#### **First-aid Measures**

#### Inhalation

Remove source of exposure or move to fresh air. Call a Poison Centre or doctor if you feel unwell or are concerned.

#### **Skin Contact**

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Call a Poison Centre or doctor if you feel unwell or are concerned. Clean clothing, shoes and leather goods.

#### **Eye Contact**

If eye irritation persists, get medical advice/attention. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.

#### Ingestion

Rinse mouth with water. Call a Poison Centre or doctor if you feel unwell or are concerned.

## Most Important Symptoms and Effects, Acute and Delayed

If swallowed: There are 3 stages of effects, which can overlap. Early symptoms can include upset stomach, slurred speech, clumsiness, drowsiness, and convulsions. Second stage symptoms can include rapid heartbeat and breathing, bluish lips and skin, fluid in the lungs and heart failure. In the last stage, there can be kidney stones and kidney damage with lower back pain, and increased then decreased urine production. There may be delayed nervous system effects such as paralysis of the face, clumsiness, impaired hearing and blurred vision. Death can occur at any stage.

## **Immediate Medical Attention and Special Treatment**

#### **Target Organs**

Digestive system, nervous system, heart, digestive system, kidneys, skin.

#### **Special Instructions**

Product Identifier: TURBO POWER ALL SEASON Antifreeze/Coolant

SDS No.: 0749 Page 02 of 08

The signs and symptoms in ethylene glycol poisoning are those of metabolic acidosis, central nervous system depression and kidney injury. Clinical chemistry may reveal anion-gap metabolic acidosis and uremia. Treatment with ethanol to inhibit the metabolism of glycol to oxalate. Early administration of ethanol may counter the toxic effects of ethylene glycol (cardiopulmonary effects attributed to metabolic acidosis and renal damage). Hemodialysis or peritoneal dialysis have been of benefit. Pre-existing respiratory and skin disorders may be aggravated by over-exposure to this product. Treat symptomatically and supportively.

#### **Medical Conditions Aggravated by Exposure**

Dermatitis.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

#### **Extinguishing Media**

## **Suitable Extinguishing Media**

Carbon dioxide, dry chemical powder or appropriate foam.

#### **Unsuitable Extinguishing Media**

None known.

#### **Specific Hazards Arising from the Chemical**

Can ignite if strongly heated.

In a fire, the following hazardous materials may be generated: irritating chemicals.

#### Special Protective Equipment and Precautions for Fire-fighters

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills. See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

## Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

#### **Environmental Precautions**

Do not allow into any sewer, on the ground or into any waterway.

#### Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

#### **SECTION 7. HANDLING AND STORAGE**

#### **Precautions for Safe Handling**

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### **Conditions for Safe Storage**

Product Identifier: TURBO POWER ALL SEASON Antifreeze/Coolant

SDS No.: 0749 Page 03 of 08

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

	ACGII	ACGIH TLV®		OSHA PEL		AIHA WEEL	
Chemical Name	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA	
Ethylene glycol	10 mg/m3	100 mg/m3	Not established	50 ppm			
Sodium Salt of Boron Acid	Not established	Not established	Not established	Not established			

## **Appropriate Engineering Controls**

The hazard potential of this product is relatively low. General ventilation is usually adequate. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.

#### **Individual Protection Measures**

#### **Eye/Face Protection**

Not required but it is good practice to wear safety glasses or chemical safety goggles.

#### **Skin Protection**

Wear chemical protective clothing e.g. gloves, aprons, boots.

Nitrile rubber.

#### **Respiratory Protection**

Not normally required if product is used as directed. For non-routine or emergency situations: wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

#### **Basic Physical and Chemical Properties**

Appearance Clear green liquid.
Odour Not available
Odour Threshold Not available
pH Not available

Melting Point/Freezing Point -13 °C (9 °F) (Ethylene glycol) (melting); -13 °C (9 °F) (Ethylene glycol) (freezing)

Initial Boiling Point/Range 197 °C (387 °F)

Flash Point 111 °C (232 °F) (closed cup) (Ethylene glycol)

**Evaporation Rate** < 0.01

Flammability (solid, gas) Not applicable

Upper/Lower Flammability or

**Explosive Limit** 

21.6 - 22.0% (Ethylene glycol) (upper); 3.2% (Ethylene glycol) (lower)

Vapour Pressure 0.090 mm Hg (0.012 kPa) at 20 °C (Ethylene glycol)

Vapour Density (air = 1) 2.14 (estimated)

Relative Density (water = 1) 1.12 - 1.15 at 20 °C (Ethylene glycol)

**Solubility** Not available in water; Soluble in all proportions in ketones (e.g. acetone).

Partition Coefficient, -1.36 at 20 °C (Ethylene glycol)

n-Octanol/Water (Log Kow)

**Auto-ignition Temperature** 398 °C (748 °F) (Ethylene glycol)

Product Identifier: TURBO POWER ALL SEASON Antifreeze/Coolant

SDS No.: 0749 Page 04 of 08

**Decomposition Temperature** Not available

Viscosity 18.86 mm2/s at 20 °C (estimated) (kinematic); 21 mPa.s at 20 °C (estimated)

(dynamic)

Other Information

Physical State Liquid

Molecular Weight Not available

## **SECTION 10. STABILITY AND REACTIVITY**

#### Reactivity

Not reactive under normal conditions of use.

## **Chemical Stability**

Normally stable.

#### **Possibility of Hazardous Reactions**

None known.

#### **Conditions to Avoid**

None known.

#### **Incompatible Materials**

Slightly reactive or incompatible with the following materials: oxidizing agents (e.g. peroxides), strong acids (e.g. hydrochloric acid), strong bases (e.g. sodium hydroxide).

Not corrosive to metals.

## **Hazardous Decomposition Products**

None known.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Likely Routes of Exposure**

Skin contact; ingestion.

#### **Acute Toxicity**

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)	
Ethylene glycol	2725 mg/m3 (rat) (4-hour exposure)	4700 mg/kg (rat)	9530 mg/kg (rabbit)	
Sodium Salt of Boron Acid	Not available	Not available	Not available	

LC50: Not applicable.

LD50 (oral): Not applicable. LD50 (dermal): Not applicable.

#### Skin Corrosion/Irritation

May cause moderate or severe irritation based on information for closely related materials. Symptoms include pain, redness, and swelling.

## Serious Eye Damage/Irritation

May cause serious eye irritation based on information for closely related materials. Symptoms include sore, red eyes, and tearing.

## STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Product Identifier: TURBO POWER ALL SEASON Antifreeze/Coolant

SDS No.: 0749 Page 05 of 08

At high concentrations vapour may cause lung injury, nose and throat irritation. Symptoms may include coughing, shortness of breath, difficult breathing and tightness in the chest. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

#### **Skin Absorption**

At high concentrations may cause Symptoms may include redness, rash, swelling and itching.

## Ingestion

Toxic, can cause death based on information for closely related materials. depression of the central nervous system, and effects on the heart and kidneys. In some cases, there may be delayed effects on the nervous system. There are 3 stages of effects, which can overlap. Early symptoms can include upset stomach, slurred speech, clumsiness, drowsiness, and convulsions. Second stage symptoms can include rapid heartbeat and breathing, bluish lips and skin, fluid in the lungs and heart failure. In the last stage, there can be kidney stones and kidney damage with lower back pain, and increased then decreased urine production. There may be delayed nervous system effects such as paralysis of the face, clumsiness, impaired hearing and blurred vision. Death can occur at any stage.

#### **Aspiration Hazard**

Not known to be an aspiration hazard.

## STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause dermatitis. Symptoms may include dry, red, cracked skin (dermatitis). Harmful effects on the kidneys.

#### Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

#### Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Ethylene glycol	Not Listed	A4	Not Listed	Not Listed
Sodium Salt of Boron Acid	Not Listed	A4	Not Listed	Not Listed

#### **Reproductive Toxicity**

## **Development of Offspring**

If swallowed: at high concentrations animal studies show effects on the offspring. Known to cause: decreased weight. Embryotoxic (late resorptions) teratogenic(external, soft tissue and skeletal defects) may harm the unborn child. (Sodium Salt of Boron Acid)

#### **Sexual Function and Fertility**

May cause effects on sexual function and/or fertility. (Sodium Salt of Boron Acid)

#### Effects on or via Lactation

No information was located.

## **Germ Cell Mutagenicity**

Not known to be a mutagen.

#### **Interactive Effects**

No information was located.

#### Other Information

TOXIC SUBSTANCE: KEEP AWAY FROM ANIMALS AND SMALL CHILDREN.

## **SECTION 12. ECOLOGICAL INFORMATION**

#### **Toxicity**

## **Acute Aquatic Toxicity**

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Ethylene glycol	18500 mg/L (Oncorhynchus mykiss (rainbow	74000 mg/L (Daphnia magna (water flea); 24 hr)		

Product Identifier: TURBO POWER ALL SEASON Antifreeze/Coolant

SDS No.: 0749 Page 06 of 08

	trout); 96-hour; fresh water)		
Sodium Salt of Boron Acid	Not available	Not available	

## **Chronic Aquatic Toxicity**

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Ethylene glycol	39140 mg/L (Oncorhynchus mykiss (rainbow trout))		24000 mg/L (Daphnia magna (water flea))	
Sodium Salt of Boron Acid	Not available	Not available		

#### Persistence and Degradability

No information was located.

#### **Bioaccumulative Potential**

This product and its degradation products are not expected to bioaccumulate.

#### **Mobility in Soil**

No information was located.

#### Other Adverse Effects

There is no information available.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14. TRANSPORT INFORMATION**

Not regulated under Canadian TDG Regulations.

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
US DOT	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID (Ethylene glycol)	9	III

# **Special Precautions** for User

Please note: In single containers of 5000 lbs capacity or less this product is exempt from DOT regulations (non regulated). Does not require label or placards. Regulated Quantity (RQ)= 5000 lbs (2268 kg) (as ethylene glycol) For bulk shipments equal to or greater than Regulated Quantity (RQ), please adhere to classification as outlined in DOT Classification section.

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15. REGULATORY INFORMATION**

# Safety, Health and Environmental Regulations Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

Product Identifier: TURBO POWER ALL SEASON Antifreeze/Coolant

SDS No.: 0749 Page 07 of 08

#### **USA**

#### Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

## **Additional USA Regulatory Lists**

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause birth defects.

## **SECTION 16. OTHER INFORMATION**

**SDS Prepared By** Compliance and Regulatory Department

Phone No. 905-878-5544

Additional Information We are committed to uphold the Industry Consumer Ingredient Communication Voluntary

Initiative.

Please send us your request by visiting our website at www.recochem.com.

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without

respect to order of predominance.

**Disclaimer** Notice to reader: To the best of our knowledge, the information contained herein is accurate.

> However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are

described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: TURBO POWER ALL SEASON Antifreeze/Coolant

SDS No.: 0749

